


EXPANDED PTFE FILMS

E5 (0.5G/CM³)

E5 (0.5G/CM³) Expanded PTFE Film is manufactured by **Saint-Gobain**® Performance Plastics Corporation, Tape Solutions business, and is intended to meet the most demanding requirements for the coaxial cable industry. The **Saint-Gobain** extrusion process provides the longest splice free/joint free lengths and highest uniform physical properties supporting low loss high frequency coaxial cables. **Norgard**® E5 Film is manufactured with ASTM D4895 compliant resins.

**Previously known as*

FLUOROWRAP® E5 EXPANDED PTFE FILM



FEATURES AND BENEFITS

- Low signal loss in coaxial cables
- Long joint free lengths
- Tight thickness tolerance
- Physical property uniformity
- High tensile strength

AVAILABILITY

- Available on industry standard 3" (76 mm) ID cores in flat- pad, traverse wound and StablEdge™ packages
- Slit widths are available at 0.10" (2.5 mm) and wider
- Customized solutions available

APPLICATIONS

- Coaxial cables

*Pictures shown are for illustration purpose only.

TYPICAL PROPERTIES

Thickness	2.0 mil	4.0 mil	5.0 mil	10.0 mil	Unit
Thickness (metric)	0.051	0.101	0.127	0.254	mm
Thickness Tolerance	± 0.2	± 0.2	± 0.2	± 0.3	mil
	± 0.005	± 0.005	± 0.005	± 0.008	mm
Density	0.5	0.5	0.5	0.5	g/cm ³
Tensile Strength MD (minimum)	3,500	3,000	3,000	2,500	psi
	25	20	20	17	MPa
Tensile Strength TD (minimum)	80	100	125	150	psi
	0.6	0.7	0.9	1.0	MPa
Elongation (minimum)	65	70	80	80	%
Joint Free Lengths	1,700	1,100	900	750	LY
	1,500	1,000	820	685	M

The values presented are typical values and should not be used for specification purposes. Contact your **Saint-Gobain** Tape Solutions representative for more information.

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to your actions or inactions, including your use, design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: This document should not be considered a warranty or a guarantee. The descriptions of the Product provided hereinabove may vary based on specifications requested and testing protocols. Typically, Saint-Gobain warrants that product(s) will meet mutually agreed specifications at delivery and Saint-Gobain honors any breach of warranty claims for six (6) months from delivery of the products. If a product is determined to be nonconforming with its warranty, Saint-Gobain's sole obligation is, at its option, to either replace the nonconforming products or reimburse the purchase price for the same.

The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR USE.

Form #1921 | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain Tape Solutions or affiliates, part of Saint-Gobain group.



TAPE SOLUTIONS

North America | South America
Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com