

CHR® K201/K202

Polyimide, Silicone Adhesive Tape

CHR K201 and K202 are manufactured by **Saint-Gobain®** Performance Plastics Corporation, Tape Solutions business, and come with a special grade polyimide backing material with a high-temperature silicone pressure-sensitive adhesive.

Features/Benefits

These tapes have excellent mechanical properties. **CHR** K201 offers high conformability and outstanding resistance to cut-through, and is impact and abrasion resistant. Burning of the adhesive on either tape forms a non-conductive ash. Polyimide film coated with silicone adhesives comply with UL510 standards for flame retardancy and 180°C operating environment.

Availability

Factory stock for **CHR** K201 and K202 is in master log rolls 33 m long × 991 m (36 yd × 39 in) wide. Rolls can be slit from 12.7 mm (0.5 in) wide up to full width. These tapes are available only without a liner.

Applications

CHR K201 and K202 are often used for applications that require protection from high temperature and/or chemical resistance. Chosen for gold finger protection during wave solder, high temperature masking during powder coating and tool-die-mould protection in composite moulding.



CHR K201/K202 Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

| Product Number | K201 | K202 |
|--------------------------------|-------------------------------|-------------------------------|
| Backing Material | Film-Polyimide | Film-Polyimide |
| Adhesive Type | Silicone | Silicone |
| Total Thickness mm (mil) | 0.064 (2.5) | 0.089 (3.5) |
| Backing Thickness mm (mil) | 0.025 (1.0) | 0.051 (2.0) |
| Adhesive Thickness mm (mil) | 0.038 (1.5) | 0.038 (1.5) |
| Adhesion to Steel N/cm (oz/in) | 2.2 (20) | 2.5 (23) |
| Tensile Strength N/cm (lb/in) | 44 (25) | 70 (50) |
| Elongation (% at break) | 80 | 90 |
| Operating Temperature °C (°F) | -73 to +260 (-100 to +500) | -73 to +260 (-100 to +500) |
| Colour | Amber | Amber |

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to your actions or inactions, including your use, design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: This document should not be considered a warranty or a guarantee. The descriptions of the Product provided hereinabove may vary based on specifications requested and testing protocols. Typically, Saint-Gobain warrants that product(s) will meet mutually agreed specifications at delivery and Saint-Gobain honors any breach of warranty claims for six (6) months from delivery of the products. If a product is determined to be nonconforming with its warranty, Saint-Gobain's sole obligation is, at its option, to either replace the nonconforming products or reimburse the purchase price for the same.

The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR USE.

Form #1118 | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain Tape Solutions or affiliates, part of Saint-Gobain group.



TAPE SOLUTIONS

North America | South America
Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com