

3134

MOPP FILM TAPE



Saint-Gobain® Performance Plastics  
Corporation, Tape Solutions business

### General Description

55 micron tensilized MOPP film coated with a high quality acrylic adhesive system. Intended for temporary holding and surface protection. Clean removal from glass, ABS, stainless steel, painted steel, etc.

### Features

- Good adhesion and tack
- Good ageing and chemical resistance
- Residue-free removal

### Applications

- Glass industry
- Furniture industry
- Home appliance industry

### Technical Data

Property	Value
Product Type	Single coated
Backing Type	MOPP film
Adhesive Type	Removable acrylic
Color	Blue
Backing Thickness	0,055 mm
Total Thickness	0,075 mm
Peel Adhesion at 180° On Steel	2.50 N/cm
Tensile Strength	200.00 N/cm
Rolling Ball Tack	< 10 cm
Elongation at Break	45%
Short Time Temperature Resistance	120 °C
Temperature Resistance	-50°C/+70 °C
Shelf Life	12 months
Standard Length	66 m
Standard Width	1250 mm



\* International harmonized test methods: ASTM D-1000, PSTC, EN 60454-2.



**TAPE SOLUTIONS**

North America | South America  
Europe | Asia

For more information, please visit  
[tapesolutions.saint-gobain.com](http://tapesolutions.saint-gobain.com)

All statements and information listed above regarding this product are typical values for general guidance, these data have not to be intended as conformity specification. These suggestions are based on tests we believe reliable, but are not guaranteed for accuracy and completeness. The user must test, evaluate and validate this product before the use, assuming risks and liability of such use. This document may be revised without prior notice. Suggested storage temperature is between 10°C and 30°C with 50% relative humidity.

**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

**WARRANTY:** For a period of 12 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1677EU | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain.