

7010

DOUBLE COATED POLYESTER TAPE

General Description

12 micron polyester film coated on both sides with a high performance, high tack solvent based acrylic adhesive and protected by a polycoated siliconized release paper liner. Designed for splicing, bonding and lamination of foams, papers, plastics, films and foils. Performs well on difficult surfaces and it is intended for tough bonding applications. Excels where UV and temperature resistance is needed.

Features

- Thin and conformable
- Great initial tack and adhesion
- Good UV and environmental resistance
- Permanent adhesion to a variety of difficult substrates

Applications

- Splicing industry

Technical Data

Property	Value
Product Type	Double coated
Backing Type	PET film
Adhesive Type	Modified acrylic
Color	Clear
Liner Type	Bi-siliconized paper
Liner Color	White
Backing Thickness	0,012 mm
Total Thickness	0,152 mm
Peel Adhesion at 90° On Steel	6.00 N/cm
Rolling Ball Tack	< 10 cm
Static Shear	> 168 hours
Short Time Temperature Resistance	160 °C
Temperature Range	-30 °C/+130 °C
Shelf Life	12 months
Standard Length	50 m
Standard Width	1000 mm



* International harmonized test methods: ASTM D-1000, PSTC, EN 60454-2..

All statements and information listed above regarding this product are typical values for general guidance, these data have not to be intended as conformity specification. These suggestions are based on tests we believe reliable, but are not guaranteed for accuracy and completeness. The user must test, evaluate and validate this product before the use, assuming risks and liability of such use. This document may be revised without prior notice. Suggested storage temperature is between 10°C and 30°C with 50% relative humidity.

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 12 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1871EU | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain.



TAPE SOLUTIONS

North America | South America
 Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com