

CHR[®] 2302

UHMW Pressure Sensitive Adhesive Tape

CHR 2302 is manufactured by **Saint-Gobain[®]** Performance Plastics Corporation, Tape Solutions business, and comes with UHMW (Ultra High Molecular Weight) polyolefin film coated with acrylic adhesive.

Features/Benefits

CHR 2302 exhibits excellent abrasion resistance and a low coefficient of friction, making it an excellent protection for surfaces or bearings that experience heavy wear. It is more economical than PTFE tapes. The high heat ranges noted in this data sheet, high-tack acrylic adhesive adheres readily to most dry, clean surfaces, firmly anchoring the product in place.

Availability

Factory stock for **CHR 2302** is in master log form 33 m × 889 mm (36 yd × 35 in). Rolls can be slit in widths ranging from 6.35 mm to 889 mm (0.25 in to 35 in). The product is supplied with a blue poly-film inter-liner, which intends to protect the adhesive, facilitate die cutting, and peels off easily. Craft paper liner is also available upon request.

Applications

CHR 2302 can be used to provide an abrasion-resistant, anti-stick, anti-friction surface at temperatures up to 107°C (225°F). It is frequently used to line chutes and conveyors. The product is often applied to guide rails to reduce noise levels in glass bottling plants. This tape is also used to replace desk drawer bearings, and to provide silky smooth, friction free drawer movement.



CHR 2302 Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	2302-3R	2302-5R	2302-10R	2302-20R
Backing Material	Film-UHMW	Film-UHMW	Film-UHMW	Film-UHMW
Adhesive Type	Acrylic	Acrylic	Acrylic	Acrylic
Total Thickness mm (mil)	0.114 (4.5)	0.165 (6.5)	0.292 (11.5)	0.546 (21.5)
Backing Thickness mm (mil)	0.076 (3.0)	0.127 (5.0)	0.254 (10.0)	0.508 (20.0)
Adhesive Thickness mm (mil)	0.038 (1.5)	0.038 (1.5)	0.038 (1.5)	0.038 (1.5)
Adhesion to Steel N/cm (oz/in)	3.8 (35)	4.9 (45)	5.5 (50)	5.5 (50)
Tensile Strength N/cm (lb/in)	35 (20)	70 (40)	140 (80)	254 (145)
Elongation (% at break)	300	350	425	500
Operating Temperature °C (°F)	-40 to +107 (-40 to +225)	-40 to +107 (-40 to +225)	-40 to +107 (-40 to +225)	-40 to +107 (-40 to +225)
Colour	Natural	Natural	Natural	Natural

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to your actions or inactions, including your use, design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: This document should not be considered a warranty or a guarantee. The descriptions of the Product provided hereinabove may vary based on specifications requested and testing protocols. Typically, Saint-Gobain warrants that product(s) will meet mutually agreed specifications at delivery and Saint-Gobain honors any breach of warranty claims for six (6) months from delivery of the products. If a product is determined to be nonconforming with its warranty, Saint-Gobain's sole obligation is, at its option, to either replace the nonconforming products or reimburse the purchase price for the same.

The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR USE.

Form #1155 | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain Tape Solutions or affiliates, part of Saint-Gobain group.



TAPE SOLUTIONS

North America | South America
Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com