

CHR[®] G SERIES

Glass-Cloth Pressure Sensitive Adhesive Tape

CHR G551, G561, G565 and G569 are manufactured by **Saint-Gobain**[®] Performance Plastics Corporation, Tape Solutions business, and comes with electrical grade fibreglass cloth backing coated with clear pressure-sensitive adhesive.

Features/Benefits

CHR G551, G561, G565 and G569 feature a tough abrasion resistance and excellent mechanical and electrical properties. They are also highly conformable and non-corrosive. **CHR** G565 and G569 meet Underwriters Laboratories Guide OANZ2, and File E51201 specifications. They are manufactured with non-halogen materials.

Availability

Factory stock for **CHR** G551 is in master rolls 33 m and 55 m × 1194 mm wide (36 yd and 60 yd × 47 in) wide, G561 in 33 m × 610 mm (36 yd × 24 in) wide, G565 in 33 m and 55 m lengths × 610 mm (36 yd and 60 yd × 24 in) wide and **CHR** G569 in 55 m and 33 m lengths × 584 mm (60 yd and 36 yd × 23 in) wide. Rolls can be slit in widths ranging from 6.35 mm (0.25 in) to full width. They are available with or without a liner.

Applications

CHR G551, G561, G565 and G569 are intended to offer excellent solvent and flagging resistance. The high conformance and strength/ weight ratio makes **CHR** G551, G561, G565 and G569 good candidates for oil and motor applications.



CHR G Series Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	G551	G561	G565	G569
Backing Material	Glass-Cloth	Glass-Cloth	Glass-Cloth	Glass-Cloth
Adhesive Type	Thermosetting Rubber	Silicone	Silicone	Acrylic
Total Thickness mm (mil)	0.178 (7.0)	0.178 (7.0)	0.178 (7.0)	0.178 (7.0)
Backing Thickness mm (mil)	0.114 (4.5)	0.114 (4.5)	0.114 (4.5)	0.114 (4.5)
Adhesive Thickness mm (mil)	0.064 (2.0)	0.064 (2.0)	0.064 (2.0)	0.064 (2.0)
Adhesion to Steel N/cm (oz/in)	5.5 (50)	3.8 (35)	3.8 (35)	3.3 (30)
Tensile Strength N/cm (lb/in)	263 (150)	263 (150)	263 (150)	263 (150)
Dielectric Strength (volts)	3,500	4,500	4,500	3,000
Direct Electric Corr.	1.0	1.0	1.0	1.0
Operating Temperature °C (°F)	-18 to +177 (0 to +350)	-73 to +260 (-100 to +500)	-73 to +260 (-100 to +500)	-29 to +177 (-20 to +350)
Insulation Class °C	130	180	200	155
Chlorides	-	-	-	<50
Colour	White	White	White	White

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to your actions or inactions, including your use, design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: This document should not be considered a warranty or a guarantee. The descriptions of the Product provided hereinabove may vary based on specifications requested and testing protocols. Typically, Saint-Gobain warrants that product(s) will meet mutually agreed specifications at delivery and Saint-Gobain honors any breach of warranty claims for six (6) months from delivery of the products. If a product is determined to be nonconforming with its warranty, Saint-Gobain's sole obligation is, at its option, to either replace the nonconforming products or reimburse the purchase price for the same.

The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR USE.

Form #1126 | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain Tape Solutions or affiliates, part of Saint-Gobain group.



TAPE SOLUTIONS

North America | South America
Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com