

CHR® M SERIES

5 Mil Polyester Pressure Sensitive Adhesive Tape

CHR M-Series (5 Mil PET with Adhesive) is manufactured by **Saint-Gobain®** Performance Plastics Corporation, Tape Solutions business, and comes with polyester film with either rubber or silicone pressure-sensitive adhesive.

Features/Benefits

Polyester backings offer low cost effective holding for materials and resist damage from sharp edges. M895 offers superior bonding to a wide variety of treated papers, films and foils. Have a super quick-stick silicone adhesive system and the polyester backing/silicone adhesive combination is highly conformable. Recommended for all splicing applications, including in oven splices where good wet out capabilities are critical. M855 rubber adhesive is specially formulated to use as a flash mask protection tape in metal or composite bonding. The non-silicone adhesive eliminates silicone contamination and is specially formulated to remove cleanly from most surfaces after up to 4.0 hours at 177°C. Polyester backing resists damage from sharp edges, and protects tool surfaces from abuse and adhesive flash in vacuum bag sealing. Also, polyester backings offer low cost, effective positioning tape for composite lay-ups prior to bag sealing. This tape will function at temperatures up to 130°C.

Availability

Both M895BL and M855GN are available in master log form 33 m × 965 mm (36 yd × 38 in) wide. Rolls can be slit from 6.35 mm to 965 mm (0.25 in to 38 in) wide. M895 is in master log form 33 m × 965 mm (36 yd × 38 in) wide. Rolls can be slit from 12.7 mm to 965 mm (0.5 in to 38 in) wide. M855 and M895 are available with or without a liner.

Applications

M855 Polyester film offers an economical method to hold, insulate and/or protect materials. M895 is designed as a quick stick polyester splicing tape most often used in the graphic arts industry.



CHR M Series 5 Mil Polyester Tape Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	M855	M895
Adhesive Type	Rubber	Silicone
Total Thickness mm (mil)	0.178 (7.0)	0.165 (6.5)
Adhesive Thickness mm (mil)	0.051 (2.0)	0.038 (1.5)
Adhesion to Steel N/cm (oz/in)	0.7 (6.4)	3.3 (30)
Tensile Strength N/cm (lb/in)	175 (100)	175 (100)
Elongation (% at break)	100	100
Dielectric Strength (volts)	10,000	10,000
Operating Temperature °C (°F)	-18 to +177 (0 to +350)	-73 to +177 (-100 to +350)
Insulation Class (°C)	130	130
Colour	Green	Blue



TAPE SOLUTIONS

North America | South America
Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to your actions or inactions, including your use, design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: This document should not be considered a warranty or a guarantee. The descriptions of the Product provided hereinabove may vary based on specifications requested and testing protocols. Typically, Saint-Gobain warrants that product(s) will meet mutually agreed specifications at delivery and Saint-Gobain honors any breach of warranty claims for six (6) months from delivery of the products. If a product is determined to be nonconforming with its warranty, Saint-Gobain's sole obligation is, at its option, to either replace the nonconforming products or reimburse the purchase price for the same.

The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR USE.

Form #1107 | © Saint-Gobain February 2025 | All the mentioned trademarks are registered trademarks of Saint-Gobain Tape Solutions or affiliates, part of Saint-Gobain group.