



Tape Solutions for Automotive Exterior Bonding

Tape Solutions for Automotive Exterior Bonding

Saint-Gobain® has been partnering with OEM's and Tier Suppliers for over 60 years to design and develop bonding and sealing solutions for the automotive industry. This long history, coupled with unparalleled access to unique foam polymers and adhesive chemistries, allows us to deliver the best product for your specific application. Our diverse portfolio of **Norbond®** Acrylic and Polyurethane Tapes offers a range of options for attaching many exterior components, including emblems and nameplates, body side moldings, wheel flares, and pillar appliques.

Primerless Attachment Tapes

Norbond Acrylic Primerless Grade Tapes offer outstanding viscoelastic and adhesion properties to provide the ideal bonding solution for many automotive exterior applications. The adhesive technology is designed for strong primerless adhesion to challenging Medium Surface Energy (MSE) substrates while still meeting the tough demands of OEM specifications. These tapes are characterized by their fast adhesion build, reaching high peel performance within 20 minutes. The conformable cores are engineered for cohesive failure under many conditions, while still offering excellent die-cuttability and static shear resistance. Primerless attachment saves time and complexity while reducing exposure to harsh chemicals in the production environment.

Norbond Z100 Series: A transparent transfer adhesive tape especially designed for applications on MSE substrates, like PC-ABS, ASA or anodized aluminum without pre-treatment of surfaces. This tape is characterized by short-term adhesion build and balanced performance between high peel and high shear strength. Its good resistance against environmental influences and excellent adhesion on a variety of automotive paint systems make Z100 the ideal choice for demanding automotive applications.

Norbond Z2000 Series: Featuring a symmetric design, Z2000 is optimized for strong adhesion to MSE substrates without the use of adhesion promoter. Z2000 is characterized by fast short-term adhesion build and excellent peel adhesion to automotive paint systems, as well as MSE plastics such as ABS and ASA. Engineered for systematic cohesive failure under high stress conditions, this tape is ideal for pillar appliques, spoilers, fender vents, and window trim profiles.

Norbond Z3100 Series: Featuring a differential coating, Z3100 is characterized by its excellent adhesion of Low Surface Energy (LSE) plastics such as PP-EPDM, to automotive paint systems or MSE plastics such as ABS and ASA. Engineered for reliable performance in application temperatures up to 90°C, this tape is ideal for wheel flares, rocker panels and body side molding.

Traditional Attachment Tapes

Norbond Polyurethane Tapes combine a high-density, conformable polyurethane foam substrate with high-performance acrylic adhesive on both sides. The foam substrate absorbs and distributes stress forces over the entire bond line. These tapes have excellent adhesion to automotive clear coat systems, but may require use of adhesion promoter or surface treatment for adequate bond to plastic substrates on the Non-Liner Side (NLS)¹.

Norbond E500 and F500 Series: These polyurethane tapes are uniquely designed for nameplate and emblem attachment. The soft, deep black core offers great conformability and excellent die-cuttability, while exhibiting strong pluck and shear resistance and limited movement under stress. The wide range of available standard gauges (up to 3 mm), make this a versatile option for challenging part designs.

Norbond Traditional Acrylic Grade Tapes offer outstanding viscoelastic and adhesion properties to provide ideal bonding performance for many automotive exterior trim and nameplate applications. These tapes incorporate a general purpose acrylic adhesive, which delivers good performance on many OEM clear coats and primed plastics⁽¹⁾ and the firmer core brings good shear resistance and good die-cuttability.

Norbond Z1000 Series: A gray, double-sided, acrylic foam tape with great tensile adhesion strength and static shear resistance for automotive exterior applications. This acrylic core tape offers improved peel resistance and elongation, for decorative trims such as pillar appliques, and badging.

Norbond Z1200 Series: Formulated for durable, long-lasting adhesion, Z1200 exceeds automotive standards for shear strength and bonding to high surface energy substrates. Its unique self-stick core is designed for high shear resistance and allows for easy die-cutting, making it ideal for locator pin assembly applications.

Norbond Adhesion Promoters

Norbond Adhesion Promoters are formulated for use with acrylic pressure-sensitive adhesive systems, such as those used on **Norbond** attachment tapes. When applied to plastic substrates, they can help raise the surface energy in order to improve the ultimate bond strength of the tape. Formulations with UV detection additives are also available to aid in processing.

2287A: This formulation is designed for MSE substrates such as rigid PVC, ABS, and Polycarbonate.

Material Selection Guide

	Tape Core Material	Product Series	Color	Adhesive Construction	Standard Available Thickness (mm)										Performance Characteristics (Typical of 1.1 mm)				Common Applications			
					0.1	0.5	0.6	0.8	1.14	1.52	1.6	2.0	2.3	3	90° Peel Adhesion (N/cm)			Static Shear 80°C / 500g				
															LS to Painted Panel (20 min)	LS to Painted Panel (72 hr)	NLS to Unprimed Plastic (72 hr)					
Primerless Grade Tapes	Acrylic	Z100	Transparent	Single Layer Transfer	Z101													11	15	16	> 7 days (on stainless steel)	Lamination of sealing foams, profiles, and thin MSE components
		Z2000	Gray	Symmetric to MSE		Z2005		Z2008	Z2011	Z2015		Z2020						24	35	36 (on ABS)	> 7 days (on ABS)	Primerless attachment of MSE components
		Z3100	Dark Gray	Differential MSE to LSE					Z3111									37	37	40 (on PP-EPDM)	> 7 days (on PP-EPDM)	Primerless attachment of LSE components
Traditional Grade Tapes	Polyurethane	E500	Dark Black	Symmetric		E520		E530	E545		E562		E590	E5120			8	10		> 7 days (on painted panel)	Emblem and nameplate attachment	
		F500	Dark Black	Symmetric					F545								10	18		> 7 days (on painted panel)	Emblem and nameplate attachment	
	Acrylic	Z1000	Gray	Symmetric			Z1006	Z1008	Z1011									11	13		> 7 days (on painted panel)	Small to medium trim attachment
		Z1200	Gray	Single Layer		Z1220												7	9		> 7 days (on painted panel)	Locator pin attachment

LS - Liner Side Adhesive | NLS - Non-Liner Side adhesive | MSE - Medium Surface Energy | LSE - Low Surface Energy
 (1) Depending on your performance requirements and the type of plastic, an adhesion promoter may be necessary. Testing is recommended on your particular substrate. Please contact our Application Engineering group for further support.
 (2) Available Liner Configurations: Please check individual product TDS for options.

Your Partner in Custom Tape Solutions

A custom tape solution can pay for itself many times over thanks to the process and product improvements it can provide. Tape development engineers will work with partners to design an economical but highly effective tape product.

Even with endless permutations of industrial tapes available there is only one company that can deliver a custom-made tape with optimal adhesive, the perfect backing materials, seamless process integration and superb performance.

To learn more about how **Saint-Gobain** can help solve tape and materials engineering challenges, call us or visit us online.

Distributed by:

Scan to visit our website:



Saint-Gobain Tape Solutions

North America | South America | Europe | Asia

For more information, please visit
tapesolutions.saint-gobain.com

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1584 | © Saint-Gobain December 2023 | All the mentioned trademarks are registered trademarks of Saint-Gobain Tape Solutions or affiliates, part of Saint-Gobain group.