

## CHR<sup>®</sup> H7525/H7575

### Glass-Silicone Pressure Sensitive Adhesive Tape

**CHR** H7525 and H7575 (HVOF) are heavy-duty pressure-sensitive tapes used for thermal spray masking. They are manufactured by combining multiple layers of silicone rubber, aluminium foil and fibreglass coated with aggressive high-temperature silicone adhesive. HVOF means High Velocity Oxygen Fuel spray technique.

### Features/Benefits

**CHR** H7525 and H7575 have exceptional abrasion resistance and adhesion properties, which allows the tapes to wear very well during the spraying process. These tapes are also very conformable and can be used for many part configurations. They can continuously withstand temperatures up to 260°C.

### Availability

Factory stock for **CHR** H7525 is in master rolls 33 m x 914 mm (36 yd x 36 in) and 33 m x 1219 mm (36 yd x 48 in) wide for H7575. Rolls can be slit in widths ranging from 6.35 mm (0.25 in) to full width on 76.2 mm (3.0 in) ID cores.

**CHR** H7525 and H7575 are supplied with a yellow plastic release liner.

### Applications

**CHR** H7525 and H7575 are used as high-temperature masking tapes in thermal spray and high velocity oxygenated fuel (HVOF) processes. The tapes are used to protect portions of the part being processed so that they are not exposed to spray. They are used primarily in the aircraft industry in their repair shops as well as in other markets where thermal spraying is used.



**CHR H7525/H7575 Properties**

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	H7525	H7575
Backing Material	Glass-foil-Silicone	Glass-Silicone
Adhesive Type	Silicone	Silicone
Total Thickness mm (mil)	0.445 (17.5)	0.533 (21.0)
Backing Thickness mm (mil)	0.381 (15.0)	0.445 (17.5)
Adhesive Thickness mm (mil)	0.064 (2.5)	0.089 (3.5)
Adhesion to Steel N/cm (oz/in)	5.5 (50)	5.5 (50)
Tensile Strength N/cm (lb/in)	219 (125)	315 (180)
Operating Temperature °C (°F)	-73 to +260 (-100 to +500)	-73 to +260 (-100 to +500)
Colour	White	White

**Performance Plastics - Tape Solutions**

North America | South America | Europe | Asia

For a full list of locations, please visit  
[tapesolutions.saint-gobain.com/contact-us](http://tapesolutions.saint-gobain.com/contact-us)

**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

**WARRANTY:** For a period of 6 months, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1124 | © Saint-Gobain January 2018 | **CHR** and **CHRTape** are trademarks of Saint-Gobain.